



(330) 725-4949
(330) 273-3700 Clevel.
(330) 239-4949 Akron
(330) 725-6730 Fax
(800) 433-5608

6-1-2008

CONFIDENTIAL MAJOR FLEET PRICING

TIGER GENERAL SWABMASTER SWAB RIG SPECIFICATIONS & PRICING

MAIN DRAW WORKS/DRUM NEW: SWAB MASTER MODEL

FRAME 3"X3"X1/4" SQUARE TUBING DOUBLE LADDER MAIN FRAME. 3" TUBING "U" SHAPED END FRAMES. 43 1/2" WIDE, X 70" LONG, X 40" HIGH. 3/4" THICK MOTOR MOUNT PLATE, WITH 3 FLEXIBLE MOTOR MOUNTS. BAR GRATING END COVER. STAINLESS STEEL DRIP PAN. GALVANIZED REEL SHIELD TOP, AND BRAKE END COVER

DRUM: SIZE: 35" DIA X 36 1/2" WIDE INSIDE. 8" X 1" WALL BARREL. 1" THICK STEEL END PLATES WITH 6 GUSSET PER END, REINFORCED. OVERALL LENGTH DRUM 48", 3-7/16" MAIN SHAFT WITH SEAL MASTER MP 55 PILLOW BLOCK BEARING. DRUM CAPACITY, 14,400 FT. OF 7/16". 11,000 FT. 1/2". 8,766 FT. 9/16" CABLE. NORMAL OPERATING DEPTH 7,500 FEET IN 4". WITH STD HYDRAULICS..**FLEET ANGLE SPOOLING DEVICE WITH 20" SHEAVE.

BRAKES: HYDRAULIC DISK TYPE. CARLISLE BRAND M-4 SERIES 4 PISTON CALIPER WORKING ON 20 X 3/4" ROTOR. LEVER ACTIVATED AT OPERATORS AREA. AUXILIARY HYDROSTATIC BRAKES. AUXILIARY FREE FALL HYDROSTATIC MODULATING BRAKE VALVE.

SANDLINE DRUM DRIVE PUMP: SUNSTRAND MODEL 100, 6.1 CU. IN./REV. AXIAL PISTON DESIGN PUMP. 68 GPM @ 2600 RPM DIRECT DRIVEN FROM FRONT OF TRUCK ENGINE. DRIVEN VIA TRANSFER CASE ON F-550 FOR CHASSIS. MAX PS. 7000. H.D. STAINLESS CABLE LEVER CONTROLS AT OPERATORS AREA

MOTOR: ROTARY POWER MODEL SMA 1000, 61 CU IN/REV. MOTOR DEVELOPS 3890 FT. LBS. TORQUE @ 5000 PSI, 6,057 FT. LBS. @ 7000 PSI. SINGLE LINE PULL, FIRST WRAP, 8,155 @ 7000 PSI LINE SPEED PROX 1,000 FT PER MINUTE WITH 7,500 FT OF 7/16" CABLE INSTALLED. 92% EFFICIENT! * 30% MORE USABLE POWER THAN CHAIN DRIVE DRUMS. PATENTED "FREE FALL" BYPASS VALVE. AND HYDROSTATIC BRAKE.

MAIN HYDRAULIC PLUMBING SYSTEM: MAIN DRIVE, 1" HYDRAULIC STEEL TUBING WITH 4 BOLT FLANGE "O" RINGS, COD 62, AND SAE 37 DEGREE JIC FITTINGS WHEREVER POSSIBLE. PREMIUM HOSE IN OTHER AREAS. PIPE FITTINGS ON SUCTION SIDE. 40 GALLON STEEL RESERVOIR WITH CLEAN OUT DOOR. ANTI-SWIRL SUCTION STRAINER, SITE GAUGE WITH THERMOSTAT. FILTERED VENT. 32,000 BTU ELECTRIC FAN COOLED OIL COOLER, AUTO COOLER BYPASS VALVES. CHARGE SUCTION FILTER. 50 GPM ABSOLUTE RETURN FILTER

PAGE 2 6-1-2008 TIGER GENERAL WELLTENDER SPEC'S & PRICING

AUXILIARY HYDRAULIC: AUXILIARY HYDRAULIC SYSTEM FOR HYDRAULIC CYLINDER, 8 GPM PIGGYBACK PUMP ON BACK OF MAIN PUMP. MULTI BANK # 8 "O" RING PORT SPOOL VALVE TO ACTIVATE HYDRAULIC CYLINDERS.

BODY: INTERNATIONAL CHASSIS. 170" LONG X 96" WIDE. (FORD F-550 CHASSIS 134" LONG) 3/16" DIAMOND PLATE DECK. 3" STD. CHANNEL XM, 5" CHANNEL MAIN FRAME, FULL 5" CHANNEL HEAVY DUTY HEADBOARD WITH WINDOW. REINFORCED FOR MAST REST. GALVANIZED BAR GRATING FOLD UP REAR OPERATORS WORK PLATFORM. 24 X 96, 1 1/4 X 1/4, ON IH CHASSIS. SWING FRAME 3" X 5" X 1/4" RECTANGLE TUBING GREASE FITTINGS ON SWING HINGE AND LATCHES. TWO HYDRAULIC 3" X 25" STROKE TWIN POST REAR STABILIZERS, CHROME CYLINDER SHAFTS ON STABILIZERS AND MAST RAISE CYLINDERS. SEALED TRUCK LIGHT SYSTEM. BODY UNITIZED AND BOLTED TO TRUCK FRAME, STEPS AND GRAB HANDLES TO FACILITATE ACCCESS. 2- 48" TOOL BOXES. BODY SANDBLASTED, 2 STAGE EPOXY PRIMER AND PAINTED ONE COLOR, URETHANE.

MAST: 6" X 6" X 5/16" SQUARE STEEL TUBING. 34' ON INTERNATIONAL. 32' TO TOP OF 20" CROWN SHEAVE, ON FORD F-550 4X4 CHASSIS. MAST BASE SITS ON REINFORCED BODY. MAST HYDRAULICALLY RAISED WITH 3" X 30" CYLINDER. "QUICK TILT" MAST ADJUST SYSTEM. OPERATING LOAD 30,000# WHEN PROPERLY GUYED

***TIGER GENERAL, INC. RESERVES THE RIGHT TO CHANGE & UPDATE SPEC'S AS IT SEES FIT TO DO.**

PRICING & OPTIONS

MAJOR FLEET PRICE.....262,284.00

OPTIONS; AT NET INVESTMENT PRICING;

A.	DUAL FRONT HYDRAULIC STABILIZERS, DUAL POST STYLE. 18" STROKE.....	9,396.00
B	FULL RIG & CHASSIS CANOPY, ALUMINUM.....	7,300.00
C	EXTRA TOOL BOX, 18 X 18 X 48", ..EACH,.....	738.00
D	VERTICAL 36" X 18X18" TOOL BOX, 2 SHELVES,.....	859.00
E	TALLER SWABBING MAST, 1 SHEAVE 55' TELESCOPIC MAST, 8 X 8" X 5/16" OUTER, 7 X 7 X 5/16" INNER,.....	12,425.00
F	45' PEMCO MINI DERRICK, FIXED,..... <u>PROX PRICING</u>	30,000.00
G	TOOL RACK ON SIDE.....	611.00
H	ELECTRONIC SANDLINE DEPTHOMETER.....	5,824.00
I	LUBRICATOR MOUNTED ON MAST	1,094.00
J	CABLE CONDITIONER SPRAY BAR, TANK & CONTROLS.....	1,579.00
K	OIL SAVER "SLOBBER" TANK WITH DRAIN ,.....	725.00
L	PRESSURIZED SLOBBER TANK,.....	1,248.00
M	ELECTRONIC LOAD SENSE PIN IN CROWN SHEAVE. GROSS & NET LOADS,.....	6,036.00
N	ELECTRONIC ENGINE READ OUTS AT RIG OPERATORS,.....	1,121.00
O	ENCLOSED CROWN SHEAVE WITH DRAIN TO SLOBBER TANK,.....	STANDARD
P	MORE POWERFUL DRIVE MOTOR, 98 CU. IN. 6160 FT. LB. TORQUE @ 5,000 PSI,.....	3,496.00
Q	MORE POWERFUL DRIVE MOTOR 122 CU. IN. 7710 FT. LBS. TORQUE & 5,000 PSI.....	4,231.00
R.	90 SERIES 6000 PSI SUNSTRAND PUMP 6.1.....	STANDARD
S	90 SERIES 6000 PSI SUNSTRAND PUMP 7.93.....	3,498.00
T	OPERATORS CABIN, REINFORCE FIBERGLASS. 70" LONG, 93" WIDE 87" HIGH, OPERATORS WINDOWS 1 DOOR SIDE WINDOWS, STORAGE/BENCH SEAT BEHIND OPERATOR. 1 DUPLEX 110 VOLT PLUG. 30,000 BTU AIR CONDITIONER HEATER. STORAGE SHELVES. MOUNTED, PAINTED,.....	37,471.00
U	HYDRAULIC DRIVE 6 KW FULL TIME GENERATOR,.....	15,409.00
V	ELECTRONIC LOAD SENSE SYSTEM LED READ OUTS, .WITH DEPTHOMETER DEPTH IN & OUT OF WELL, GROSS & NET LOADS. ALL TIED TOGETHER. WARNING HORN ON DEPTHOMETER. ELECTRONIC DIGITAL CHARGE & SYSTEM PRESSURE GAUGES. ELECTRONIC DIGITAL TUBING AND CASING WELLHEAD PRESSURE GAUGES ALL DOWN LOADABLE TO YOUR LAPTOP. NO LOGGING SOFTWARE NET INVESTMENT.....	16,220.00
W	LOGGING SOFTWARE INCLUDED TO WRITE YOUR OWN PROGRAMS. MANAGEMENT SOFTWARE AVAILABLE SOON, **(<u>ESTIMATED PRICING</u>).....	12,346.00

PAGE 4 6-1-2008 TIGER GENERAL SWABMASTER SPEC'S & PRICING

- X 10,000# HYDRAULIC WINCH MOUNTED ON SWING FRAME WITH 150' 3/8" CABLE WITH HOOK. SWIVEL PULLEY UNDER CROWN,.....9,084.00
- Y 15,000# WARN ELECTRIC FRONT MOUNT WINCH WITH 150' CABLE,.....4,078.00
- Z **SPECIAL 7/32 CABLE DRUM:** SIZE: 35" DIA X 36 1/2" WIDE INSIDE. 12" X 7/8" WALL BARREL. 1" THICK STEEL END PLATES WITH 8 GUSSETS PER END, REINFORCED. OVERALL LENGTH DRUM 48" , 3-7/16" MAIN SHAFT WITH SEAL MASTER MP 55 PILLOW BLOCK BEARING. DRUM CAPACITY, 29,000 FT 7/32. 14,400 FT. OF 7/16". 11,000 FT. 1/2". 8,766 FT. 9/16" CABLE. NORMAL OPERATING DEPTH 17,000 FEET WITH 7/32 LINE IN 2". WITH STD HYDRAULICS. NET INVESTMENT,.....3,656.00
- G1 AUXILIARY HYDRAULIC SYSTEM WITH AIR SHIFT PTO, 20 GPM PUMP, 2 BANK SPOOL VALVE WITH RELIEF 30 GAL RESERVOIR, PLUMBING, OIL,.....6,998.00
- G2 WORK LIGHTS. 4- 3000 C.P. MOUNTED, FUSED, SWITCHED,.....1,123.00
- G3 HAVIS SPECIAL SCENE LIGHTS, 45,000 CP 12 VOLT, **EACH,.....1,248.00
- G4 LED LIGHTS,.....311.00
- G-4 ADD RATTLE GUARD COATING TO FLOOR AND TAILBOARD,.....935.00

******NEED SOMETHING, JUST ASK.** OUR UNIQUE DESIGNS ALLOW US TO GIVE YOU WHATEVER OPTIONS YOU NEED TO MAKE MORE MONEY.

***CALL MARK OVERHOLT FOR ANY SPECIAL OPTIONS AVAILABLE. *** 800 433 5608**