TIGER GENERAL INC. 6867 WOOSTER PIKE MEDINA OHIO 44256 330-725-4949 PHONE 330-725-6730 FAX WWW/TIGERGENERAL.COM

٠,

### FLEET SPEC/PRICE SHEET TEC WELL SERVICE

#### 5/25/2001

TIGER GENERAL WELLTENDER SWABBING RIG SPECIFICATIONS & PRICING 16,000 FOOT CAPACITY

#### MAIN DRAWORKS/DRUM

FRAME: 4"X 4" SQUARE TUBING, "LADDER STYLE" REINFORCED, INNER FRAME. SHIELD & DRIP TRAY. WHEEL STYLE MOTOR \* FLEET ANGLE AUTO SPOOLING DEVICE.

DRUM DIRECT DRIVE, HYDRAULIC. DRUM SIZE: 40" DIA X 50" WIDE. 10" OD X 8" I.D. BARREL, 1" THICK REIN-FORCED FLANGES, 3 15/16" MAIN SHAFT ON ROLLER AND BALL BEARINGS. PATENTED "FREE FALL" BYPASS VALVE. CAPACITY 15,500 FT. OF 9/16" NORMAL OPERATING DEPTH 16,000 FT. \*NOTE: MAX CAPACITY REQUIRES 196 MOTOR & 12.2 PUMP

BRAKES: HYDRAULIC DISK TYPE. CARLISLE BRAND A-4 SERIES 4
PISTON CALIPER WORKING ON 19" ROTOR. LEVER ACTIVATED.
AUXILIARY HYDROSTATIC BRAKES.

### SANDLINE DRUM DRIVE

PUMP: SUNSTRAND 90 SERIES 7.93 CU.IN. 102 GPM @ 3,000 RPM. PUMPS DRIVEN FROM TIGER GENERAL POWER TOWER 370 HP ENCASED, TIMING BELT DRIVE. INSTALLED IN MAIN CHASSIS DRIVELINE.

MOTOR: ROTARY POWER MODEL SMA 153 CU.IN. MOTOR DEVELOPS 9,639 FT.LBS. TORQUE @ 5000 PSI, 20,498 POUNDS LINE PULL FIRST WRAP, 240 RPM, AVERAGE LINE SPEED 760 FT/MIN. FROM ENGINE TO DRUM BARREL, SYSTEM 92% EFFICIENT! THATS 30% MORE USABLE POWER THAN CHAIN DRIVE DRUMS. BIGGER SYSTEM AVG LINE SPEED 940 FT.MIN.

16,000 FT CAPACITY

PAGE 2 5/25/2001

## MAIN HYDRAULIC PLUMBING SYSTEM:

MAIN DRIVE, HYDRAULIC STEEL TUBING WITH SAE "O" RING AND SAE 37 DEG. JIC FITTINGS WHEREVER POSSIBLE. PREMIUM HOSE IN OTHER AREAS. PIPE FITTINGS ON SUCTION SIDE. 30 GALLON STEEL RESERVOIR WITH CLEAN OUT DOOR. ANTI-SWIRL, SITE GAUGE WITH THERMOMETER, VENT. 190 SQ. IN. OIL COOLER, AUTO COOLER BYPASS VALVES. PATENTED "FREEFALL" BYPASS VALVE. ONE 50 GPM SUCTION FILTER, ONE 50 GPM RETURN LINE FILTER.

- AUXILIARY HYDRAULIC: AUXILIARY HYDRAULIC SYSTEM FOR HYDRAULIC CYLINDERS, 10 GPM PIGGYBACK PUMP ON BACK OF MAIN PUMP. OR OTHER AUX PUMP. MULTI BANK 1/2" PORT SPOOL VALVE TO ACTIVATE HYDRAULIC CYLINDERS.
- BODY; 162" LONG x 96" WIDE, 3/16" DIAMOND PLATE DECK. 3"
  CHANNEL XM, 5" CHANNEL MAIN FRAME, GUSSETS, FULL HEAVY
  DUTY HEADBOARD WITH WINDOW SCREEN REINFORCED FOR MAST
  REST. 24" x 96" 1-1/4"x 1/4" BAR GRATING FOLD UP WORK
  PLATFORM. SWING FRAME 3" x 5" x 1/4" RECTANGLE.

  TUBING SET FOR BREAK-OVER MAST. GREASE FITTINGS ON
  SWING HINGE AND LATCHES.TWO HYDRAULIC 25" STROKE TWIN
  POST REAR STABILIZERS, CHROME CYLINDER SHAFTS ON
  STABILIZERS AND MAST RAISE CYLINDERS. SEALED TRUCK
  LITE, LIGHT SYSTEM. BODY UNITIZED AND BOLTED TO TRUCK
  FRAME, STEPS AND GRAB HANDLES TO FACILITATE ACCESS. 148" TOOL BOX. BODY ACID WASHED, PRIMED AND PAINTED ONE
  COLOR, ACRYLIC ENAMEL.
- MAST: 7" x 7" x 1/4" SQUARE STEEL TUBING, 37' TO TOP OF 22"
  CROWN SHEAVE, MAST STICK OUT FROM SWING FRAME 48"
  BASE SECTION SETS ON REINFORCED BODY. HYDRAULICALLY
  RAISED WITH 3" x 30" CYLINDER. "QUICK TILT" MAST
  ADJUST. OPERATING LOAD 48,000# WHEN PROPERLY GUYED.
- \* TIGER GENERAL RESERVES THE RIGHT TO UPDATE & CHANGE SPECIFICATIONS AS IT SEES FIT TO DO.

## PAGE 3 5/21/2001 16,000 CAPACITY

# OPTIONS; INCLUDED IN TOTAL PRICE.

- B. PREMIUM PRIMER, POLYURETHANE PAINT TEC WELL'S ONE COLOR O CHOICE
- G. MORE POWERFUL ROTERY POWER MOTOR 196 CU.IN. 12,348 FOOT POUNDS TORQUE @ 5000 PSI, 17,248 FOOT LBS @ 7000 PSI
- G-1 TWIN 6.1 CU.IN. SUNSTRAND PUMPS
- U. ELECTRONIC ENGINE ADAPTER CONTROLS
- \* 12" LONGER BODY, ADD 12" AHEAD OF REEL. TOTAL BODY LENGTH 174" CHASSIS W.B. 200"

**NEW INTERNATIONAL 4900 CHASSIS,	NET,47,162.00 <b>176,877.00</b>
NOTES FROM MEETINGS; ALL PRICING AT "NET"	
ADD STAINLESS TELESCOPIC MAST, 7 X 7 X 1/4" 6 X 6 1/4" 20' SECTIONS, 50' TO TOP OF CROWN, WILL TRY TO FIND LONGER TUBES TO GET TO 48-50 CAN ORDER 2 20" SECTIONS OF 7X7, WELD TOGETHER FOR 50' MAST*****(WILL TRY FOR 24' SECTION. IF SO, DELETE 927.00 COSTS)	
**TRUCK COLOR TO BE WHITE, RIG COLOR TO BE TEC WELL ORANGE** CHANGE TO SPLIT HYD CONTROL FOR FORWARD & REVERSE CUT CONTROL HANDLES OFF ON SPOOL VALVE ADD STEPS AT FRONT OF BODY, RIGHT ADD 1" PIPE RAIL ON BED, UP 4" WITH POSTS EVERY 16" PROX, ADD PROVISIONS FOR ELECTRONIC WELL INDICATORS, ADD PROVISIONS TO ADD LOAD, SEED, & DEPTH GAUGES,	N/C N/C N/C N/C
ADD PROVISIONS TO ADD LOAD, SEED, & DEFTH GAUGES,	

"TEC WELL 5171"

MAY 2 | 2001

MARK OVERHOLT TIGER GENERAL, INC. 6867 WOOSTER PIKE MEDINA, OH 44256 330-725-4949 FAX 725-6730