



(330) 725-4949
 (330) 273-3700 Cleve.
 (330) 239-4949 Akron
 (330) 725-6730 Fax
 (800) 433-5608

CONFIDENTIAL MAJOR FLEET PRICING

SWABMASTER MACHINE
Price Effective Date 10/01/2016

DATE: 06/24/2021

PRICING GOOD FOR 30 DAYS FROM DATE OF QUOTE

		PRICE	COST
SwabMaster 16k - 9/16			339,843.00
MAIN DRAW WORKS: FORMED "U" DESIGN WITH 3/4" END PLATES AND 4" x 4" X 1/4" TUBE FLANGE SUPPORTS WITH CENTRALLY LOCATED 4" DRAIN. STANDARD REEL SHEILD IS INCLUDED. WINCH FRAME AND REEL GUARD SAND BLASTED AND COATED WITH TWO STAGE EPOXY PRIMER AND URETHANE PAINT SYSTEM.			
DRUM: HYDRAULICALLY POWERED DIRECT DRIVE DRUM. DRUM HAS 40" DIAMETER 1" FLANGES WITH 8 REINFORCEMENT GUSSETS ON EACH END WITH A 10" OD X 8" I.D. BARREL TOTAL WIDTH 50". BRAKE END AND DRIVE END STUB SHAFTS 3-15/16" DIAMETERS ARE SUPPORTED IN FRAME WITH BLUE BRUTE QAF20A315 SPERICAL BEARINGS. THE DRUM HAS A CABLE CAPACITY OF 17,000 FT. OF 9/16" CABLE ENABLING NORMAL OPERATING DEPTH OF 16,000 FT. *NOTE: CABLE SIZE AND LENGTH EFFECT PERFORMANCE. OUR SYSTEM CAN BE CUSTOMIZED TO ALLOW FOR CHANGES TO DELIVER THE POWER & SPEED YOU REQUIRE.			
BRAKES: HYDROSTATIC DISC BRAKE FOR DOWN HOLE CONTROL. TWO CARLISLE BRAND M-4 SERIES 4 PISTON CALIPERS WORKING ON 20" ROTOR THAT ARE AIR ACTUATED FOR HOLDING & EMERGENCY.			
SANDLINE DRUM DRIVE: HYDRAULIC DIRECT DRIVE TO DRUM AND POWERED BY A SAI 3600 RADIAL PISTON MOTOR. THE SAI MOTOR IS A 221.9 CUBIC INCH DISPLACEMENT THAT PRODUCES 16,780 FT. LBS. OF TORQUE AT 6,000 PSI AND A RATED SPEED OF 200 RPM'S. THE PUMPS ARE TWIN 10.1 CUBIC INCH/REV SUNSTRAND "H" SERIES EACH FOR A TOTAL DISPLACEMENT OF 20.1 CU.IN./REV THAT PROVIDES 180 GPM @ 2,100 RPM.			
CABLE SPOOLING: FLEET ANGLE AUTO SPOOLING DEVICE USING AN ENCLOSED 20" SHEAVE ON A CHROMED 4" SHAFT WITH DRIP OILIER			
MAIN HYDRAULIC PLUMBING SYSTEM: HYDRAULIC STEEL TUBING UTILIZED ON THE MAIN DRIVE WITH CODE 62 FLANGE FITTINGS, SAE "O" RING, SAE 37 DEGREE AND JIC FITTINGS WHEREVER REQUIRED. PREMIUM HIGH PRESSURE HOSE IS USED IN OTHER AREAS. PIPE FITTINGS ARE USED ON THE SUCTION SIDE. RESERVOIR IS A STEEL 60 GALLON CAPACITY WITH CLEAN OUT DOOR. ANTI-SWIRL INTERNAL PLATE, FILTERED VENT, AND A SITE GAUGE WITH THERMOMETER. HYDRAULIC SYSTEM COOLING IS ACHIEVED BY USING RUST FREE ALUMINUM CORED GRILLED GUARD COOLER WITH FAN THAT IS RATED AT A HEAT EXCHANGE RATE OF 290,000 BTU @ 110F. AUTO COOLER BYPASS VALVE. PATENTED "FREE-FALL" BYPASS VALVE. SYSTEM FILTRATION HAS 2 SUCTION FILTERS ON PUMPS AND 65 GPM RETURN LINE FILTER TO RESERVOIR.			

	AUXILIARY HYDRAULIC: HYDRAULIC CYLINDERS ARE ACTUATED BY A 2.6 GPM AUXILIARY PIGGYBACK PUMP ON BACK OF MAIN PUMP AND MULTI-BANK ½" PORTED SPOOL VALVES WITH INTEGRATED LOCK VALVES FOR ALL CYLINDERS.		
	BODY: DIMENSIONS ARE 222" LONG x 102" WIDE. BODY HAS 5" CHANNEL MAIN FRAME WITH 3" CHANNEL CROSSMEMBERS, 3/16" DIAMOND PLATE DECK, HEAVY DUTY 5" CHANNEL HEADBOARD REINFORCED FOR MAST REST AND A 24" x 101" GALVANIZED GRATING - W19 X 2 REAR WORK PLATFORM. LEFT SIDE FOLD DOWN 24" X 72" SIDE OPERATOR PLATFORM OPTION. SWING FRAME 6" X 4" x 1/4" RECTANGLE TUBING CONSTRUCTION WITH 4" X 3/8" WALL MAST HINGE WITH GREASE FITTINGS ON HINGE & MAST LATCH. BODY IS OF UNITIZED CONSTRUCTION AND BOLTED TO TRUCK FRAME. TWO 3" X 25" STROKE PREMIUM HYDRAULIC TWIN POST REAR STABILIZERS WITH CHROME CYLINDER SHAFTS ON STABILIZERS. SEALED TRUCK LIGHT SYSTEM. BODY STEPS AND GRAB HANDLES TO FACILITATE ACCESS. (1) 60" AND (1) 48" TOOL BOX ARE LOCATED UNDER BODY. BODY IS SAND-BLASTED, PRIMED WITH 2 STAGE EPOXY PRIMER AND PAINTED ONE COLOR INDUSTRIAL URETHANE PAINT. FRONT BUMPER IS A HEAVY DUTY OIL FIELD BUMPER SWEEP BACK DESIGN WITH TOW FLAP.		
	MAST: 8" x 8" x 1/4" SQUARE STEEL TUBING, 42' TO TOP OF 20" ENCLOSED CROWN SHEAVE. MAST STICK OUT FROM SWING FRAME APPROXIMATELY 48". QUICK TILT MAST ADJUST ON REINFORCED BASE AT REAR OF BODY. OPERATING LOAD 38,000# WHEN PROPERLY GUYED. HYDRAULICALLY RAISED WITH 5" x 30" CYLINDER WITH CHROMED SHAFT.		
	CONTROLS: ALUMINUM CONTROL PANEL HAS ELECTRONIC THROTTLE & PUMP CONTROLS, LIQUID FILLED GAUGES FOR SYSTEM PRESSURE AND 2 CHARGE PRESSURES, HOUR METER, ENGINE START STOP SWITCH. HYDRAULIC STABILIZERS AND MAST RAISE CYLINDER VALVE BANK CONTROLS LOCATED IN REAR TAILBOARD AND OFFSET TO THE LEFT.		
	OPTIONS TO YOUR SWAB MASTER MACHINE BELOW		
	* TIGER GENERAL RESERVES THE RIGHT TO UPDATE OR CHANGE SPECIFICATIONS AS REQUIRED WITHOUT NOTICE.*		
100	TELESCOPIC MAST- 55' UNDER 20" CROWN SHEAVE - MAST 8" X 8" X 1/4"W OUTER/ 7" X 7" X 3/8" INNER		\$18,667.00
110	45' PEMCO MINI FIXED DERRICK - APPROXIMATELY	\$62,000.00	
120	10,000# HYDRAULIC WINCH MOUNTED ON SWING FRAME WITH 150' 3/8" CABLE/HOOK/SWIVEL PULLEY		\$8,959.00
130	MODIFIED CREW CAB WITH OPERATORS CABIN, RAISED ROOF WITH WINDOW		\$11,927.00
140	OPERATORS CABIN, REINFORCE FIBERGLASS WITH STEEL INTERNAL FRAME. 70" LONG, 93" WIDE 87" HIGH, OPERATORS WINDOWS 1 DOOR SIDE WINDOWS, STORAGE/BENCH SEAT BEHIND OPERATOR. 1 DUPLEX 110 VOLT PLUG. 30,000 BTU AIR CONDITIONER HEATER. STORAGE SHELVES. INVERTER. MOUNTED, PAINTED	\$38,827.00	
150	FULL RIG & CHASSIS CANOPY - ALUMINUM	\$10,993.00	
160	REAR SWING FRAME MOUNT ALUMINUM GRATING PLATFORM	\$981.00	
170	DUAL FRONT HYDRAULIC STABILIZERS, DUAL POST STYLE. 16" STROKE	\$12,458.00	
180	DUAL FRONT MANUAL CRANK STABILIZERS	\$2,977.00	
190	CABLE CONDITIONER SPRAY BAR, TANK & CONTROLS		\$1,883.00

200	OIL SAVER "SLOBBER" TANK WITH DRAIN	\$790.00	
210	<i>PRESSURIZED OIL SAVER SLOBBER TANK WITH DRAIN</i>		\$1,791.00
220	TOOL BASKET OPEN BAR GRADING BOTTOM	\$1,889.00	
230	SIDE MOUNT TOOL RACK	\$683.00	
240	DECK MOUNTED TUBING RACK	\$1,588.00	
250	VERTICAL 18" X 18" X 36" TOOL BOX WITH 2 SHELVES	\$879.00	
260	TOOL BOX 18" X 18" X 48"	\$790.00	
270	FRONT BUMPER SKID PLATE AND INSTALLATION	\$1,829.00	
280	FRONT STEEL BUMPER PLATFORM TO ACCESS CROWN	\$1,466.00	
310	SAFETY HAND RAILS - 1-1/4" PULL OUT ALONG LEFT AND RIGHT SIDE OF RIG	\$1,566.00	
320	<i>WORK FLOOD LIGHTS. 6- 3000 C.P. MOUNTED, FUSED, SWITCHED</i>		\$1,685.00
330	ELECTRONIC SANDLINE DEPTHOMETER	\$4,829.00	
340	ELECTRONIC LOAD SENSE PIN IN CROWN SHEAVE FOR GROSS AND NET LOADS	\$4,829.00	
350	<i>ELECTRONIC ENGINE READ OUTS AT RIG OPERATORS CONTROL PANEL</i>		\$969.00
360	<i>TIGER VISION - ELECTRONIC LOAD SENSE & DEPTHOMETER LED READ OUTS. DEPTH IN & OUT OF WELL. GROSS & NET LOADS. WARNING HORN ON DEPTHOMETER. ELECTRONIC DIGITAL CHARGE, SYSTEM PRESSURE GAUGES. ELECTRONIC DIGITAL TUBING AND CASING WELLHEAD PRESSURE GAUGES ALL DOWN LOADABLE TO YOUR LAPTOP. **NO LOGGING SOFTWARE**</i>		\$19,829.00
370	LOGGING SOFTWARE TO WRITE YOUR OWN PROGRAMS MANAGEMENT SOFTWARE AVAILABLE SOON **ESTIMATED PRICING**	\$9,877.00	
380	INTERNATIONAL ON COMMAND MAINTENANCE SOFTWARE	\$2,763.00	
390	<i>LUBRICATOR 2 STAGE 3SCH80, (2) HU3F400 HAMMER UNIONS, PAINTED AND MOUNTED ON MAST</i>		\$1,998.00
400	SWAB TOOLS - (3) SINKER BAR 1-3/4"X5', 3/4 BOX AND PINS, JARS 1-5/8X24", AND 2" SWAB MANDREL DBL.2	\$3,977.00	
420	ROPE SOCKET 9/16"	\$219.00	
450	<i>DOUBLE OIL SAVER UNIT COMPLETE WITH OIL SAVER PUMP ASSY., 50' HOSE, GAUGE, AND FITTINGS</i>		\$3,327.00
470	BOP 01-00050 2.44"VB, 2000EP, LP15, STD 0-1 1/2" GIC, 3-1/2LP MXF, AND (1)O-RING SET AND (2) SEALS	\$1,288.00	
480	ESPAR DIESEL FIRED ENGINE WATER HEATER WITH TIMER - INCLUDES HYDRAULIC RESERVOIR IN LOOP	\$6,519.00	

490	FUEL TANK HEATER - ARTIC FOX	\$1,495.00	
500	HYDRAULIC AUXILIARY AND CHARGE PUMP BYPASS KIT TO ASSIST COLD WEATHER START	\$1,980.00	
510	SYNTHETIC OIL - SHELL TELLUS S4 ME 46	\$1,896.00	
520	AUXILIARY HYDRAULIC SYSTEM WITH AIR SHIFT PTO, 20 GPM PUMP, 2 BANK SPOOL VALVE WITH RELIEF, 30 GALLON RESERVOIR, PLUMBING, AND OIL	\$7,428.00	
530	ZINC RICH POWDER PRIMER, 2 STAGE EPOXY PRIMER, HIGH SOLIDS EUROTHANE TOP COAT		N/C
540	16,000 FT OF 9/16" CABLE INSTALLED ON WINCH DRUM		\$29,000.00
		OPTIONS TOTAL	\$439,878.00
		2020 INTERNATIONAL CREW CAB TANDEM CHASSIS PER SPECS To Follow	\$125,000.00
		TOTAL NET INVESTMENT	\$564,878.00