


TIGER GENERAL LLC



6867 Wooster Pike
Medina, Ohio 44256
www.tigergeneral.com
e-mail: tigergeneral.com

(330) 725-4949
(330) 273-3700 Cleve.
(330) 239-4949 Akron
(330) 725-6730 Fax
(800) 433-5608



Model Profile 2020 HV607 SBA (HV607)

AXLE CONFIG:	6X4
APPLICATION:	Flat Dump
MISSION:	Requested GVWR: 58000. Calc. GVWR: 54000 Calc. Start / Grade Ability: 18.15% / 2.13% @ 55 MPH Calc. Geared Speed: 79.9 MPH
DIMENSION:	Wheelbase: 246.00, CA: 135.00, Axle to Frame: 120.00
ENGINE, DIESEL:	{Cummins L9 370} EPA 2017, 370HP @ 2000 RPM, 1250 lb-ft Torque @ 1400 RPM, 2100 RPM Governed Speed, 370 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 3000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, w/ 5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends Gear Ratio: 4.88
CAB:	Conventional 6-Man Crew Cab
TIRE, FRONT:	(2) 315/80R22.5 Load Range L G751 MSA (GOODYEAR), 484 rev/mile, 68 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G G622 RSD (GOODYEAR), 497 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson HAS-402-55} 40,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers, Mounted Inboard
PAINT:	Cab schematic 100WL Location 1: 9219, Winter White (Std) Chassis schematic N/A



OIL FIELD SERVICE RIGS



"BRIDGER" DUMP TRAILERS,
ROLL OFF TRAILERS, PUP TRAILERS

Over 80 Years of productive service

HEAVY DUTY TRUCK / TRAILER SALES, FINANCING & LEASING

Diesel Truck Service, Engine Overhauls, all types of Welding, Job Shop Machine Shop Services, Driveshaft Repairs,
Manufacturer of Oil Field Truck Equipment, Truck Bodies, Frame Stretches

<u>Code</u>	<u>Description</u>
HV60700	Base Chassis, Model HV607 SBA with 246.00 Wheelbase, 135.00 CA, and 120.00 Axle to Frame.
1AND	AXLE CONFIGURATION {Navistar} 6x4
	<u>Notes</u>
	: Pricing may change if axle configuration is changed.
1CAJ	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.433" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL
1LLA	BUMPER, FRONT Steel, Swept Back
1SAL	CROSSMEMBER, REAR, AF (1)
1UAM	FRAME EXTENSION, FRONT Integral; 27" In Front of Grille
1WGY	WHEELBASE RANGE 221" (560cm) Through and Including 262" (665cm)
2ARV	AXLE, FRONT NON-DRIVING {Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,000-lb Capacity
3770	SPRINGS, FRONT AUXILIARY Rubber
3ADD	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)
4EBS	AIR DRYER {Bendix AD-9} with Heater
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4JCJ	BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM Capacity
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab
4VKG	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab
5710	STEERING COLUMN Tilting and Telescoping
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PSA	STEERING GEAR {Sheppard M100} Power
6DDE	DRIVESHAFT SYSTEM {Dana Spicer} SPL170XL with SPL170XL Interaxle Shaft in lieu of 1810 Driveshaft with 1710 Interaxle Shaft
7BEV	AFTERTREATMENT COVER Steel, Black
7BKS	EXHAUST SYSTEM Single Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
7WBA	TAIL PIPE (1) Turnback Type, Bright, for Single Exhaust
7WBS	MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel
7WDM	EXHAUST HEIGHT 10'
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
8518	CIGAR LIGHTER Includes Ash Cup
8541	HORN, ELECTRIC (2) Disc Style
8718	POWER SOURCE Cigar Type Receptacle without Plug and Cord
8GGG	ALTERNATOR {Delco Remy 36SI} Brushless, 12 Volt 165 Amp. Capacity, Pad Mount, with Remote Voltage Sensor
8MSH	BATTERY SYSTEM {Fleotrite} Maintenance-Free, (4) 12-Volt 2640CCA Total
8RML	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/3.5MM Auxiliary Input, MP3, Apple Device Play & Control, Bluetooth for Phone & Music
8RMZ	SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars
8THB	BACK-UP ALARM Electric, 102 dBA
8WCK	POWER SOURCE, TERMINAL TYPE 2-Post
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8XBK	SWITCH, AUXILIARY Switch 40 amp Circuit for Customer Use; Includes Wiring Connection at PDC and Control in Cab
8XGJ	BATTERY BOX Steel with Plastic Cover, 30" Wide, 2, 3 or 4 Battery Capacity, Mounted Left Side Under Cab
8XGT	TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

<u>Code</u>	<u>Description</u>
8XHD	BATTERY DISCONNECT SWITCH 300 Amp; Cab Mounted, Disconnects Charging Circuits; Locks with Padlock
8XHN	HORN, AIR Black, Single Trumpet, with Lanyard Pull Cord
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HAN	INSULATION, UNDER HOOD for Sound Abatement
9HBM	GRILLE Stationary, Chrome
9HBN	INSULATION, SPLASH PANELS for Sound Abatement
9WAC	BUG SCREEN Mounted Behind Grille
9WBC	FRONT END Tilting, Fiberglass, with Three Piece Construction; for WorkStar/HV
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100 <u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WL"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12849	BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines
12851	PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted
12EHY	ENGINE, DIESEL {Cummins L9 370} EPA 2017, 370HP @ 2000 RPM, 1250 lb-ft Torque @ 1400 RPM, 2100 RPM Governed Speed, 370 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed
12UWZ	RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core with Internal Water to Oil Transmission Cooler and 1167 In Charge Air Cooler
12VBG	AIR CLEANER Dual Element, with Integral Pre Cleaner
12VGZ	FEDERAL EMISSIONS {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2019
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel
12WBR	FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On)
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations
12XAT	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
13AVR	TRANSMISSION, AUTOMATIC {Allison 3000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
13WET	TRANSMISSION SHIFT CONTROL for Column Mounted Stalk Shifter
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
13WYH	TRANSMISSION TCM LOCATION Located Inside Cab
13WYU	SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming
13XAM	PTO LOCATION Dual, Left and Right Side of Transmission
14899	SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab
14GVM	AXLE, REAR, TANDEM {Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, w/.5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends . Gear Ratio: 4.88
14ULU	SUSPENSION, REAR, AIR, TANDEM {Hendrickson HAS-402-55} 40,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers, Mounted Inboard
14WMJ	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints
15924	FUEL TANK STRAPS Bright Finish Stainless Steel
15DYR	DEF TANK 9.5 U.S. Gal. 35.9L Capacity, Frame Mounted Outside Left Rail, Back of Cab
15LLY	LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 66" Back of Cab
15LMR	FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor
15SVN	FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 70 US Gal (265L), Mounted Left Side, Back of Cab
16196	CAB Conventional 6-Man Crew Cab
16615	SEAT, REAR BENCH; Omit Item
16BAM	AIR CONDITIONER with Integral Heater & Defroster

<u>Code</u>	<u>Description</u>
16GDC	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel Mounted in Instrument Panel
16HKA	IP CLUSTER DISPLAY Omit Display of Fault Codes in Instrument Cluster and Disable Blink Codes, Requires Service Tool to Retrieve and View Fault Code
16JNT	SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
16PPN	SEAT, PASSENGER {National 2000} Air-Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, Dual Shocks
16SNV	MIRRORS (2) Aero; Pedestal, Power Adjust, Heated Heads, Turn Signals, Bright Finish Heads, Black Arms, 6.3" x 13.82" Flat Glass, 6.38" x 6.18" Convex Glass Both Sides
16VKD	CAB INTERIOR TRIM Classic, for Crew Cab <u>Includes</u> : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger : DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16WBY	ARM REST, RIGHT, DRIVER SEAT
16WBZ	ARM REST, LEFT, PASSENGER SEAT
16WJV	WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature
16WKZ	KEYLESS ENTRY SYSTEM REMOTE with Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)
16WLS	FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood
16WSK	CAB REAR SUSPENSION Air Bag Type
16XJN	INSTRUMENT PANEL Flat Panel
16XWE	SUNSHADE, EXTERIOR Bright Finish; Includes Integral Clearance/Marker Lights
16ZBU	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps Per Door, for use with Crew Cab
27DUS	WHEELS, FRONT {Accuride 41730} DISC; 22.5x9.00 Rims, Polished Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DMC	WHEELS, REAR DUAL DISC; 22.5x8.25 Rims, Polished Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7372138102	(8) TIRE, REAR 11R22.5 Load Range G G622 RSD (GOODYEAR), 497 rev/mile, 75 MPH, Drive
7772548123	(2) TIRE, FRONT 315/80R22.5 Load Range L G751 MSA (GOODYEAR), 484 rev/mile, 68 MPH, All-Position

Services Section:

40128	WARRANTY Standard for HV507, HV50B, HV607 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A PDI & DOT including safety triangles and fire extinguisher * This quote has an SPA attached to it (for USA only sales). Price includes the 12% FET.
-------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------